

# Furnace Parts

Code#	Description	Mfg#
-------	-------------	------

### 440V Oval Run Capacitor

.1309775	440v 30/5 MFD	F87073054
.1309794	440v 35/5 MFD	F87073554
.1309795	440v 40/5 MFD	F87074054
.1309797	440v 45/5 MFD	F87074554
.1309798	440v 10 MFD	F87071004
.1309801	440v 7.5 MFD	F87070754
.1309799	440v 5 MFD	F87070504
.921376	TurboMini 2.5 - 15 MFD	TURBOMINI
.921379	370/440v 70/7.5 MFD	USA2222A



Oval Run Capacitor



Relay

### Relay Switch

		Type	Coil Volts	Switch	
454-3390	90-340	91	24	DPDT	1056363

### Contactors

.1308180	24v 1Pole 30A with Shunt	F87020311
.312072	24v 1 Pole 25A	1050699
.430179	24v 1 Pole 30A with Shunt	1172472



Contactors

### Transformers

	Primary Voltage	SEC Voltage	VA	RA	
454-3975	120	24	40	FM	1170003



Transformer

# Furnace Parts



Liquid Drier

Code#	Description	Mfg#
-------	-------------	------

### *Dryers Liquid*

	Vendor #	Cu. In.	FTG ODF
454-3395	DRYL083S	8	3/8-Mar



Condenser Motor

### *Condenser/Blower Motor*

.1131109	1/3-1/6 HP 2-Speed 230v 1PH 1075 RPM	F2573465
.1131113	3/4-1/5 HP 115v 1PH 1075 RPM	F2573466
.1131444	1/2-1/6 HP 115v 1 PH 1075 RPM	F2573463

# Combination Detectors

Code#	Description	Mfg#
-------	-------------	------

## **AC Powered, Digital Display, Plug-In Carbon Monoxide Alarm**

The Kidde KN-COPP-3 AC powered, plug-in carbon monoxide alarm utilizes sophisticated electronic components and unmatched sensor technology to protect you and your family from the dangers of CO. The KN-COPP-3 includes a 9V battery backup that provides continuous monitoring of CO levels, even during power outages, when AC-only units are not providing protection. The KN-COPP-3 will detect and store measured data of concentrated CO levels as low as 11 and up to 999 PPM with its peak level memory display. This alarm gives you several mounting options, including: direct-plug, a 6' power cord or table top.

### **Features and Benefits**

- **Digital Display** – Displays the level of carbon monoxide the unit is sensing. The unit updates this reading every 15 seconds.
- **Peak Level Button** – Displays the peak CO level recorded by the alarm since it was last reset or unplugged.
- **9V Battery Back-up** – Provides protection during power outage.
- **Test Button Functions** –
  - Tests the unit for proper operation
  - Resets the Carbon Monoxide alarm
- **LED Operation** –
  - Blinking dot in lower right corner of display denotes normal operation
  - Digital readout displays CO concentration in parts per million (30-900PPM)

*In alarm condition you will hear 4 quick beeps, 5 seconds off, repeat.*

454-0100	AC, Digital Display, Plug-In Carbon Monoxide Alarm	KN-COPP-3
----------	--	-----------

## **AC Powered, Plug-In CO/Gas Combination Alarm w/ Battery Backup**

The Kidde N-COEG-3 AC powered, plug-in CO and explosive gas alarm protects you and your family from two deadly threats. The N-COEG-3 includes 9V battery back up that provides protection during a power outage, when AC-only units can not provide protection. By pressing the Peak Level Button you can see the peak CO level recorded by the alarm since it was last reset or unplugged. The continuous digital display shows you the level of carbon monoxide (if any) the unit is sensing as well as if gas is present. The gas sensor is a metal oxide sensor designed to detect natural gas (methane) or propane.

### **Alarm**

- **Sounder Alarm** – The N-COEG-3 offers a loud 85-decibel pulsing alarm that will sound to alert you to a potential problem.

### **Alarm Condition**

- **Carbon Monoxide** – 4 quick beeps, followed by 5 seconds of silence, followed by 4 quick beeps. Repeat with a number showing in the display (CO concentration in ppm).
- **Gas** – one second of alarm on, one second of alarm off, repeating with “GAS” shown in display

454-0105	AC Powered, Plug-In CO/Gas Combination Alarm w/ Battery Backup	N-COEG-3
----------	--	----------



KN-COPP-3



N-COEG-3



# Combination Detectors

Code#	Description	Mfg#
-------	-------------	------



KN-COSM-XTR-B

## **Battery Operated Combination Carbon Monoxide, Fire & Smoke Alarm – Intelligent Alarm**

The Kidde KN-COSM-XTR-B uses breakthrough technology to offer a fast response to real fires, including smoldering and fast-flaming, as well as protect you from carbon monoxide and dramatically reduce the chance of nuisance alarms. The Intelligent Alarm combines the detection capabilities of an ionization smoke sensor – which is more likely to detect smaller, less visible fire particles, like those produced by flaming fires – with that of an electrochemical sensor, which is used to detect CO.

### **Features and Benefits**

- Voice Alarm – Announces the hazard type detected thereby helping to speed up the correct reaction to the hazard detected. Alarm announces “Fire Fire” when a smoke or fire hazard is detected and announces “Warning Carbon Monoxide” when a CO hazard is detected.
- Combined Carbon Monoxide and Smoke Alarm – A single unit can be installed where previously, two were needed. Reduces installation time and helps to keep home décor attractive.
- Test/Reset Button – Tests alarm circuitry and triggers the voice announcement.
- LEDs – Two LEDs are provided. Flashing green for normal operation and flashing red for alarm condition.
- Low Battery Warning – The unit warns of a low battery condition by announcing “low battery” and by initiating an alarm chirp and activating a flashing red LED.
- Battery Powered – Provides protection even during power outages when many fire and carbon monoxide incidents occur.
- Battery Safeguard – Ensures the unit cannot be accidentally mounted without batteries installed.
- Hush Feature – Temporarily silences nuisance alarms.

454-0115	Battery Operated Combination Carbon Monoxide, Fire & Smoke Alarm	KN-COSM-XTR-B
----------	--	---------------



KN-COSM-IB

## **AC Wire-in Combination Carbon Monoxide & Smoke Alarm**

The Kidde KN-COSM-IB Combination Carbon Monoxide & Smoke Alarm provides two important safety devices in a single unit. This alarm includes a voice warning system that announces “Fire, Carbon Monoxide, Low Battery or Smart Hush Activation”. The KN-COSM-IB is an easy to install alarm that is suitable for all living areas. It has a 7-year life and a 5-year limited warranty.

### **Features and Benefits**

- Smart Interconnect – Interconnects up to 24 Kidde devices (of which 18 can be initiating).
- Battery Backup (9V battery included) – Provides protection during power outages.
- Battery Lockout System – Minimized risk of mounting unit without installation of battery.
- Alarm Tamper Resist – Helps deter from tampering and theft.
- Adjustable Mounting Bracket – Makes installation fast and easy.
- Peak Level Memory – Announces “CO previously detected” if alarm had detected a CO level of 100ppm or higher since it was last reset.
- Smart Hush Feature – Silences nuisance alarms for approximately 10 minutes. (Smoke must be present before Smart Hush is activated)
- Ionization Sensor Technology – Ideal for detecting fast flaming and other types of fires.
- Test Button Functions – Tests the unit for proper operation; Resets the Carbon Monoxide alarm; Peak Level memory
- Green LED – Illuminates to indicate the unit is receiving AC power. Flashes every 5 seconds to indicate battery only mode. Flashes once per second (until reset) to indicate that the alarm sensed a smoke or CO hazard. Flashes every 2 seconds while the alarm is in HUSH mode.
- Red LED – When a dangerous level of smoke or carbon monoxide is detected the red LED will flash. If the unit malfunctions, the red LED will flash and the unit will chirp every 30 seconds.

454-0110	AC Wire-in Combination Carbon Monoxide & Smoke Alarm	KN-COSM-IB
----------	--	------------